

Product Specification Sheet

	VT-4732 30W S	MD RGB FLOC	DLIGHT WITH FF	R REMOTE CON	TROL
	Equivalent 150W	Lumens 2400	Beam Angle	Dimensions 230x136x206mm	
	RGB SKU:5755	A ⁺	2 Y E A R S WARRANTY	SENSOR COMPATIBLE	SAVE LEFTO 80% ENERGY
echnical Informatior					

Instant Start:	0-100% in lt1s	0% in It1s IP Rating:	IP65
EQ-WATTS:	150	Dimmable:	No
Watts:	30	Warranty (Years):	2
Lumens:	2400	PF:	>0.9
Beam Angle:	100	CRI:	>80
Body Type:	Die Cast Aluminium	Cast Aluminium Operation Temperate	ure: -25 to +50°c
Energy Rating:	A+	Input Power:	AC:100-240V
Long life:	50,000 Hours	00 Hours Sensor Compatibility	Yes
LED Chip Type:	SMD5730	05730	

Features

- Perfect replacement of Metal Hallide Floodlight, High Pressure Sodium Floodlight & Halogen Floodlight
 - Available in different color options of White , Day White, Warm White and RGB
 - Fascia glass sealed with SILICONE RUBBER ensuring superior waterproof /airtight performance
 - Premium Quality Aluminium Alloy body
 - High Power LED chip
 - **Corrosion Resistant**
 - Built in driver no external power supply required
 - Excellent coverage for area and façade lighting
 - Available from 10W up to 1000W
 - Application Building Façade, Sports Facilities, Industrial, Commercial Bill Boards & Hoardings, Parking Lots etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

Unit Details		Listing Details	
Gross Weight(GW) Kgs	2.1	EAN Code	3800157609517
Length(Box)mm	135	Commodity Code	9405403990
Width(Box)mm	235		
Height(Box)mm	205		
Unit CBM	0.006535		
Master Box Packaging			
Master Box Qty (Pcs Per Carton)	6		
Qty Per Pallet	150		

