

Product Specification Sheet

Outdoor Pablo Wall Light 8W 3000K 300lm IP54

Partcode: ILDEA010 / Page: 1



Discover Integral's new outdoor range. Light up the exterior of your home with these compact, stylish and contemporary LED luminaires. Weatherproof and hard-wearing, this range is designed to last against the elements while bringing a designer look to your surroundings.

Named after one of the great forefathers of Cubism, the Pablo rectangular wall light creates a striking up/down effect. The sleek design brings a contemporary feel to any area.

Watch Video

Product Details

Partcode: ILDEA010 Check Code: 326761 Range Name: Wall Light Product Type: Outdoor Warranty: 3 Years

CE / RoHS: Yes

Physical Data

Optic: Opal Polycarbonate diffuser

Material: Die cast aluminium body with powder coated finish



Product Specification Sheet

Partcode: ILDEA010 / Page: 2

Physical Data

Length: 65mm Width: 170mm Depth: 30mm

Weight (Unpackaged Single Unit): 320g

Luminaire Fixing: Wall Mounted

Electrical Data

Voltage Range: 220-240V

Power Consumption: 8.0 Watts

Driver included: Yes Electric Current: AC Ampage: 350.00mA

Frequency Range: 50/60 Hz

Power Factor: >=0.40
Dimming: Non-dimmable

LVD Certified: Yes EN: EN-60598

Light Data

Lumens: 300lm

Lumens per Watt: 38.0lm/W

Correlated Colour Temperature (CCT): 3000k

Colour Temperature: Warm White
Colour Rendering Index (CRI): >=80
LED Type: Chip-on-board (COB)
Instant on - Less than 1 second: Yes

Lifetime: 25,000 hrs


Switching Cycles: >12,500 X



Product Specification Sheet

Partcode: ILDEA010 / Page: 3

Environmental



Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 50 degrees

IP (Ingress Protection) Rating: IP54

Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788232506

Packaged Weight (Unit of 1): 345g

Length (unit of 1): 75mm Width (unit of 1): 180mm Depth (unit of 1): 40mm

Outer packaging info available on website

Product data last updated on: Wednesday, September 11, 2019 - 17:08