

SUPER SLIM 2 FLOODLIGHT IP67 7000LM 70W 4000K PIR 120° NON-DIMM 100LM/W BLACK INTEGRAL

ILFLC244



This small and compact fitting is rated at IP67 and perfect for indoor and outdoor applications. It is highly efficient and durable making it a popular choice for long life applications. It utilises branded drivers and chips and it is fully guaranteed for 3 years.

Details

Quick Order Code: 962007

Barcode: 5055788263487
Category: Luminaires
Range Name: Super Slim 2

Product Body Finish: Black

Market Segment: Residential and Commercial

Warranty (Years): 3
CE RoHS: Yes

Physical Data

Product Length (mm): 255
Product Depth (mm): 39
Product Width (mm): 222
Product Weight (g): 1272

Material: Aluminium, Tempered Glass

Construction: Aluminium die-cast heat-sink, Tempered Glass

protective front cover, Integrated driver

Bulb or Luminaire Shape: Rectangle Luminaire Fixing: Wall Mounted

Placement / Application: Indoor and outdoor, General lighting

Electrical Data

Power Consumption (W): 70
Power Factor: 0.9
Voltage Range (v): 220-240
Dimming: Non-Dimmable

Driver Included: Yes
Electric Current: AC

EN: EN-60598

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 7000 Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature Name: Cool White

Beam Angle:120Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 50000
Sensor / Overide: Yes
Switching Cycles: 25000

Environment

EN: EN-60598

LVD Certified: Yes **CE RoHS:** Yes E **New Energy Rating: EU Luminaire:** L Hg 0% (Mercury Free): Yes **IK Rating (Impact Protection): IK07** IP Rating (Back/Recessed side): **IP67 IP Rating (Ingress Protection): IP67 Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





Packaging

Package Weight (g): 1372
Package Length (mm): 260

Package Width (mm): Portal.int@38al-led.com

Package Depth (mm): 60