

SUPER SLIM 2 FLOODLIGHT IP67 7000LM 70W TUYA 3000/4000/6500K PIR 120° DIMMABLE 100LM/W BLACK INTEGRAL

ILFLC254



This small and compact fitting is rated at IP67 and perfect for indoor and outdoor applications. It is highly efficient and durable making it a popular choice for long life applications. It utilises branded drivers and chips and it is fully guaranteed for 5 years.

Details

Quick Order Code: 669462

Barcode: 5055788267737
Category: Luminaires
Range Name: Super Slim 2

Product Body Finish: Black

Market Segment: Residential and Commercial

Warranty (Years): 5
CE RoHS: Yes

Physical Data

Product Length (mm): 278
Product Depth (mm): 41
Product Width (mm): 253
Product Weight (g): 1520

Material: Aluminium, Tempered Glass

Construction: Aluminium die-cast heat-sink, Tempered Glass

protective front cover, Integrated driver

Bulb or Luminaire Shape: Rectangle Luminaire Fixing: Wall Mounted

Placement / Application: Indoor and outdoor, General lighting

Electrical Data

Power Consumption (W): 70
Power Factor: 0.9
Voltage Range (v): 220-240
Dimming: Non-Dimmable

Driver Included: Yes
Electric Current: AC

EN: EN-60598

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 7000

Correlated Colour Temperature (CCT) (K): 3000/4000/6500 CCT Switchable

Beam Angle: 120
Colour Rendering Index (CRI): 80
Frequency Range (Hz): 50/60
Instant on (Less than 1 second): Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 50000
Sensor / Overide: Yes
Switching Cycles: 25000

Environment

EN: EN-60598

LVD Certified: Yes **CE RoHS:** Yes E **New Energy Rating: EU Luminaire:** L Hg 0% (Mercury Free): Yes **IK Rating (Impact Protection): IK08** IP Rating (Back/Recessed side): **IP67 IP Rating (Ingress Protection): IP67 Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





Packaging

Package Weight (g): 1670
Package Length (mm): 285

Package Width (mm): Portal.int@g0al-led.com

Package Depth (mm): 60